



**CUSHMAN®**



# HAULER 800

**EFFICIENT AND RELIABLE, YOUR GO-TO VEHICLE.**

The Cushman® Hauler 800 is built to swiftly and easily move people and small equipment around any facility. Powered by your choice of a reliable 48-volt AC electric drivetrain or fuel-efficient 13.5 hp petrol engine, the Hauler 800 is perfectly equipped to perform a variety of duties. With a spacious dash and a range of accessories tailored for course managers, the Hauler 800 has a proven track record that can't be beat.

**LET'S WORK.**

**13.5HP**  
KAWASAKI®  
PETROL

**360KG**  
LOAD  
CAPACITY

**48V AC**  
ELECTRIC

**408KG**  
TOW  
CAPACITY





# CUSHMAN® HAULER 800



STANDARD BRUSH GUARD



RADIO CLIP



FUNCTIONAL DASH



MOISTURE METER RACK / BED DIVIDER

## OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Glove Box Mat
- Floor Mount Attachment
- Windshield
- Canopy
- Power Dump
- Long Handled Tool Holders
- Radio Holder
- Interior Tool Hook
- On-Board Charger (Elec. only)
- LED Headlights - Hi/Low
- Taillights
- Brakelights
- Hubcaps
- Ball Hitch Receiver
- Comfort Grip Steering Wheel
- High Altitude Jetting (Petrol only)
- Fuel Gauge
- Battery Fill System (Elec. only)
- Rearview Mirror
- 12-volt Outlet
- USB Port
- Unique Key Switch
- Hour Meter
- Body Colour
- Weather Enclosure
- Cab
- Ball Cage
- ROPS

	ELECTRIC	EFI PETROL
BODY & CHASSIS		
FRAME	Welded steel with E-Shield ecoat plus DuraShield powder coat	
BODY & FINISH	Injection Molded TPO (front), Injection Molded PP (rear)	
STANDARD COLOUR	Forest Green	
DIMENSIONS		
OVERALL LENGTH	280 cm (110 in)	(280 cm) 110 in
OVERALL WIDTH	125 cm (49 in)	(125 cm) 49 in
OVERALL HEIGHT	176 cm (69.5 in)	(176 cm) 69.5 in
WHEEL BASE	166 cm (65.5 in)	(166 cm) 65.5 in
FRONT WHEEL TRACK	94 cm (37.0 in)	(94 cm) 37.0 in
REAR WHEEL TRACK	97 cm (38.0 in)	(97 cm) 38.0 in
GROUND CLEARANCE	11 cm (4.3 in)	(11 cm) 4.3 in
CARGO BOX CAPACITY	0.24 m³ (8.4 cu ft)	0.24 m³ (8.4 cu ft)
POWER		
POWERTRAIN	48-Volt AC Drive	4-cycle, 24.5 ci (401cc) Cylinder
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	8.9 hp (6.6 kW) Peak	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48-Volt	Starter/Generator, Solid-State Regulator
BATTERY (QTY/TYPER)	Six 8-Volt Deep Cycle	One 12V Maintenance Free
KEY OR PEDAL START	Pedal	Pedal
OIL FILTER	n/a	Spin-On
COOLING SYSTEM	n/a	Air Cooled
FUEL CAPACITY	n/a	22.6 L (5.96 Gallon) Tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	Differential with Helical Gears
GEAR SELECTION	Dash Mount Forward-Neutral-Reverse	Forward-Reverse
REAR AXLE RATIO	16.99:1	11.47:1(Forward) 14.35:1(Reverse)
PERFORMANCE		
SEATING CAPACITY	2 Person	2 Person
CURB WEIGHT	499 kg (1101 lb)	359 kg (791 lb)
BED LOAD CAPACITY	181 kg (400 lb)	181 kg (400 lb)
VEHICLE LOAD CAPACITY	360 kg (800 lb)	360 kg (800 lb)
SPEED	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)
TOWING CAPACITY	408kg (900 lb) max	900 lb (408 kg) max
OUTSIDE CLEARANCE CIRCLE	5.8 m (18.9 ft)	5.8 m (18.9 ft)
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack and Pinion	
FRONT/REAR SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum	
PARKING BRAKE	Self-compensating, Single Point Engagement	
FRONT TYRES	K500 18 x 8.5 - 8 (6 ply rated)	
REAR TYRES	K500 18 x 8.5 - 8 (6 ply rated)	

[www.cushman.com](http://www.cushman.com) +44(0)1473 270000

©2019 Textron Specialized Vehicles Inc. All specifications subject to change.

70030-G04 (Rev. 12/2018)