



CUSHMAN®



HAULER 800 ELiTE SERIES

UNRIVALLED PERFORMANCE

Cushman® Hauler 800 ELiTE vehicles are activated by Samsung SDI lithium technology to power through your toughest work days. With faster charge times, consistent performance and increased range, the Hauler 800 ELiTE series will maximise the productivity of your crew and decrease energy costs. With a fully customisable cargo bed, highly functional dash and a broad range of accessories, Hauler 800 ELiTE vehicles have everything you need to finish job after job.

LET'S WORK.®

ELiTE

48V AC
LITHIUM

UP TO
360KG
PAY LOAD

5-YEAR
BATTERY WARRANTY

ZERO
MAINTENANCE
BATTERIES



Hauler 800 ELITE



Hauler 800X ELITE

CUSHMAN[®] HAULER 800 ELITE SERIES



BED DIVIDERS



HIGHLY FUNCTIONAL DASH



OPTIONAL BALL CAGE



OPTIONAL FLOOR MOUNT

OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Glove Box Mat
- Floor Mount Attachment
- Windshield
- Canopy
- Power Dump
- Long Handled Tool Holders
- Radio Holder
- Interior Tool Hook
- LED Headlights - Hi/Low
- Taillights
- Brakelights
- Comfort Grip Steering Wheel
- Rearview Mirror
- 12-volt Outlet
- USB Port
- Unique Key Switch
- Hour Meter
- Side Body Colour
- Weather Enclosure
- Cab
- Ball Cage
- ROPS
- Hubcaps
- Ball Hitch Receiver

	HAULER 800 ELITE	HAULER 800X ELITE
BODY & CHASSIS		
FRAME	Welded steel with E-Shield ecoat plus DuraShield™ powder coat	
BODY & FINISH	Injection Moulded TPO (front), Injection Moulded PP (rear)	
STANDARD COLOR	Forest Green or Patriot Blue	
DIMENSIONS		
OVERALL LENGTH	280 cm (110 in)	280 cm (110 in)
OVERALL WIDTH	125 cm (49 in)	125 cm (49 in)
OVERALL HEIGHT	120 cm (47 in)	130 cm (51 in)
WHEEL BASE	166 cm (65.5 in)	166 cm (65.5 in)
FRONT WHEEL TRACK	94 cm (37.0 in)	94 cm (37.0 in)
REAR WHEEL TRACK	97 cm (38.0 in)	97 cm (38.0 in)
GROUND CLEARANCE	11 cm (4.3 in)	14 cm (5.5 in)
CARGO BOX CAPACITY	237L (8.4 cu ft)	237L (8.4 cu ft)
POWER		
POWERTRAIN	48-Volt AC Drive	
VALVE TRAIN	N/A	
HORSEPOWER (KW)	8.7 kW (11.7 HP) Peak	
ELECTRICAL SYSTEM	48-Volt	
BATTERY (QTY/TYPER)	Two Lithium Ion 48 Volt	
KEY OR PEDAL START	Pedal	
OIL FILTER	n/a	
COOLING SYSTEM	n/a	
FUEL CAPACITY	n/a	
DRIVE TRAIN	Motor Shaft Direct Drive	
TRANSAXLE	Differential with Helical Gears	
GEAR SELECTION	Dash Mount Forward-Neutral-Reverse	
REAR AXLE RATIO	16.99:1	
PERFORMANCE		
SEATING CAPACITY	2-Person	
CURB WEIGHT	364 kg (803 lb)	361 kg (797 lb)
BED LOAD CAPACITY	181 kg (400 lb)	147.4 kg (325 lb)
VEHICLE LOAD CAPACITY	360 kg (800 lb)	328 kg (725 lb)
SPEED	14.5 +/-0.5 mph (23.3 +/- 0.8 kph)	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)
TOWING CAPACITY	408 kg (900 lb)	230 kg (500 lb)
OUTSIDE CLEARANCE CIRCLE	5.8 m (18.9 ft)	
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TYRES (FRONT & REAR)	20 x 8-10 (6 Ply Rated)	