



CUSHMAN®



HAULER 800X

MAKE TOUGH JOBS SIMPLE.

The Cushman® Hauler 800X features a lifted suspension that can navigate the most challenging areas of your course. With a customisable bed and practical accessories, it's designed with the versatility you need to build it your way. If topdressing, spot maintenance and debris management are critical to keeping your course in pristine condition, the Hauler 800X is ready to work.

LET'S WORK.

13.5HP
EFI PETROL

328KG
LOAD
CAPACITY

48V AC
ELECTRIC

240 L
CARGO
BED




CUSHMAN® HAULER® 800X



CUSTOMISABLE CARGO BED



FUNCTIONAL DASH



OPTIONAL HUBCAPS



OPTIONAL FLOOR MOUNT ATTACHMENT

OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Glove Box Mat
- Floor Mount Attachment
- Windshield
- Canopy
- Power Dump
- Long Handled Tool Holders
- Radio Holder
- Interior Tool Hook
- On-Board Charger (Elec. only)
- LED Headlights - Hi/Low
- Taillights
- Brakelights
- Hubcaps
- Ball Hitch Receiver
- Comfort Grip Steering Wheel
- High Altitude Jetting
- Fuel Gauge (Petrol only)
- Battery Fill System (Elec. only)
- Rearview Mirror
- 12-volt Outlet
- USB Port
- Unique Key Switch
- Hour Meter
- Body Colour
- Weather Enclosure
- Cab
- Ball Cage
- ROPS

ELECTRIC		EFI PETROL
BODY & CHASSIS		
FRAME	Welded Steel with E-Shield ecoat plus DuraShield Powder Coat	
BODY & FINISH	Injection Molded TPO (front), Injection Molded PP (rear)	
STANDARD COLOUR	Forest Green	
DIMENSIONS		
OVERALL LENGTH	280 cm (110 in)	280 cm (110 in)
OVERALL WIDTH	125 cm (49 in)	125 cm (49 in)
OVERALL HEIGHT (WITH CANOPY)	188 cm (74 in)	188 cm (74 in)
WHEEL BASE	166 cm (65.5 in)	166 cm (65.5 in)
FRONT WHEEL TRACK	94 cm (37.0 in)	94 cm (37.0 in)
REAR WHEEL TRACK	97 cm (38.0 in)	97 cm (38.0 in)
GROUND CLEARANCE	14 cm (5.5 in)	14 cm (5.5 in)
CARGO BOX CAPACITY	0.24 m³ (8.4 cu ft)	0.24 m³ (8.4 cu ft)
POWER		
POWERTRAIN	48 Volt AC Drive	4-cycle, 24.5 ci (401 cc) Cylinder
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	8.9 hp (6.6 kW) Peak	13.5 hp (10.1 kW).
ELECTRICAL SYSTEM	48 Volt	Starter/Generator, Solid-State Regulator
BATTERY (QTY/TYPE)	Six, 8-Volt Deep Cycle	One 12-Volt Maintenance Free
KEY OR PEDAL START	Pedal	Pedal
OIL FILTER	n/a	Spin-On
COOLING SYSTEM	n/a	Air Cooled
FUEL CAPACITY	n/a	22.6 L (5.96 Gal) Tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	Differential with Helical Gears
GEAR SELECTION	Dash Mount Forward-Neutral-Reverse	Forward-Reverse
REAR AXLE RATIO	16.99:1	11.47:1 (Forward) 14.35:1 (Reverse)
PERFORMANCE		
SEATING CAPACITY	2 Person	2 Person
CURB WEIGHT	509 kg (1122 lb) - Standard Batteries	376 kg (830 lb)
BED LOAD CAPACITY	147.4 kg (325 lb)	147.4 kg (325 lb)
VEHICLE LOAD CAPACITY	328 kg (725 lb)	328 kg (725 lb)
SPEED	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)
TOWING CAPACITY	230 kg (500 lb) max	230 kg (500 lb) max
OUTSIDE CLEARANCE CIRCLE	5.8 m (18.9 ft)	5.8 m (18.9 ft)
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack and Pinion	
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum	
PARKING BRAKE	Self-compensating, Single Point Engagement	
FRONT/REAR TYRES	K500 20 x 8.00 -10 (6 Ply Rated)	

www.cushman.com +44(0)1473 270000

©2019 Textron Specialized Vehicles Inc. All specifications subject to change.