



CUSHMAN



HAULER PRO

NO JOB OUT OF RANGE. NO TASK OFF LIMITS.

With its remarkable 50-mile range and 72-volt AC powertrain, the new Hauler PRO has the stamina few petrol vehicles can match. Impressive energy efficiency, low operational cost and standard features that include an on-board charger, premium turf tyres and a rear hitch receiver, make the Hauler PRO perfect for towing your greens mower to the furthest corner of your course. Optional IntelliBrake technology offers a parking brake that automatically activates whenever the vehicle is stopped. It's performance like this that's turning course managers everywhere from skeptics to believers.

LET'S WORK.

72V
AC
ELECTRIC

680KG
TOW
CAPACITY

50 MILES
PER BATTERY
CHARGE

545KG
LOAD
CAPACITY



CUSHMAN® HAULER PRO



FUNCTIONAL DASH



CARGO NET



SEALED WINDSHIELD



BED DIVIDER

OPTIONS & ACCESSORIES

- Limited Slip Differential
- Locking Glove Box
- Glove Box Mat
- Floor Mount Attachment
- Windshield
- Canopy
- Power Dump
- Long Handled Tool Holders
- Radio Holder
- Interior Tool Hook
- LED Headlights - Hi/Low
- Taillights
- Brakelights
- Hubcaps
- Comfort Grip Steering Wheel
- Fuel Gauge
- Battery Fill System
- Rearview Mirror
- 12-volt Outlet
- USB Port
- Unique Key Switch
- Hour Meter
- Body Colour (Patriot Blue, Forest Green, Ivory, Bright White, Flame Red, Orange, Black, Almond, Matte Black, Safety Yellow, Metallic Charcoal)
- Weather Enclosure
- Cab
- Ball Cage
- ROPS

BODY & CHASSIS

| | |
|-----------------|---------------------------------------------------------------|
| FRAME | Welded Steel with E-Shield e-coat plus DuraShield Powder Coat |
| BODY & FINISH | Injection Molded TPO, Painted |
| STANDARD COLOUR | Forest Green |

DIMENSIONS

| | |
|-------------------------|---------------------------------|
| OVERALL LENGTH | 302 cm (119 in) |
| OVERALL WIDTH | 125.48 cm (49.4 in) |
| OVERALL HEIGHT W/CANOPY | 179 cm (71 in) |
| WHEEL BASE | 193.04 cm (76 in) |
| FRONT WHEEL TRACK | 88.90 cm (35 in) |
| REAR WHEEL TRACK | 97.79 cm (38.5 in) |
| GROUND CLEARANCE | 11.43 cm (4.5 in) |
| CARGO BOX CAPACITY | 0.340 m ³ (12 cu ft) |

POWER

| | |
|--------------------|--------------------------------------------|
| POWER SOURCE | 72-Volts |
| MOTOR TYPE | AC Induction |
| HORSEPOWER (KW) | 22.4HP (16.7 kW) - Measured at Peak Torque |
| ELECTRICAL SYSTEM | 72 Volt |
| BATTERY (QTY/TYPE) | Nine 8-Volt Deep Cycle |
| BATTERY CHARGER | 900 Watt 72V DC |
| KEY OR PEDAL START | Pedal |
| DRIVE TRAIN | Motor Shaft Direct Drive |
| TRANSAXLE | Differential with Helical Gears |
| SPEED CONTROLLER | 350 Amp AC |
| GEAR SELECTION | Forward-Neutral-Reverse |
| REAR AXLE RATIO | 17:1 |

PERFORMANCE

| | |
|--------------------------|---------------------------------|
| SEATING CAPACITY | 2 Person |
| CURB WEIGHT | 669 kg (1475 lb) |
| BED LOAD CAPACITY | 363 kg (800 lb) |
| VEHICLE LOAD CAPACITY | 545 kg (1200 lb) |
| SPEED | 14.5 mph, (23.34 kph ± 0.8 kph) |
| PROGRAMMABLE SPEED RANGE | 5-19 mph (8-30.5 kph) |
| TOWING CAPACITY | 680 kg (1500 lb) max |
| OUTSIDE CLEARANCE CIRCLE | 6.55 m (21.5 ft) |

STEERING & SUSPENSION

| | |
|-----------------------|--------------------------------------------|
| STEERING | Self-Compensating Rack and Pinion |
| FRONT/REAR SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers |
| SERVICE BRAKE | Rear Wheel Mechanical Self-adjusting Drum |
| PARKING BRAKE | Self-compensating, Single Point Engagement |
| FRONT/REAR TYRES | 18 x 8.5-8 |