



**CUSHMAN®**

# HAULER® PRO-X



## **ZERO EMISSIONS, ZERO NONSENSE.**

The Cushman® Hauler® PRO-X has the muscle and power to keep your crew running. Equipped with a quiet, zero emissions 72V AC electric drivetrain, this vehicle will keep your crew working for up to 50 miles between charges. Give the Hauler PRO-X the ability to tackle your hardest work days.

**LET'S WORK.®**

**72V**  
AC ELECTRIC  
DRIVETRAIN

**LIFTED**  
SUSPENSION  
WITH HIGH GROUND  
CLEARANCE

**LIMITED**  
SLIP  
DIFFERENTIAL  
OPTION



# CUSHMAN® HAULER® PRO-X



LIFTED SUSPENSION WITH  
HIGH GROUND CLEARANCE



FRONT BUMPER  
& BRUSH GUARD

AGGRESSIVE-TREAD TIRES

## OPTIONS & ACCESSORIES

- Limited Slip Differential
- Locking Glove Box
- Windshield
- Roof
- Taillights
- Brakelights
- Trailer Dump (Steel and Poly)
- 14.9 cu-ft Aluminum Cargo Bed
- Roll Over Protection System with Seat Belts and Side Nets
- 12 Volt Outlet
- Body Color (Black, Patriot Blue, Ivory, White, Yellow, Orange or Custom Options)
- Turn Signal with Four-Way Flashers
- Strobe Lights
- Work Lights
- Weather Enclosure
- Defroster/Fan
- Steel Cab
- Beacon
- Ash Tray
- Differential Guard

BODY & CHASSIS	
FRAME	Welded Steel w/ DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO (Front) / Steel Base Coat/Clear Coat (Rear)
STANDARD COLOR	Forest Green
DIMENSIONS	
OVERALL LENGTH	111.0 in (282 cm)
OVERALL WIDTH	49.8 in (126 cm)
OVERALL HEIGHT	52.0 in (132 cm) (w/o Roof) / 77.0 in (196 cm) (w/ Struts & Roof)
WHEEL BASE	78.0 in (198 cm)
WHEEL TRACK	38.0 in (97 cm) Front / 38.8 in (99 cm) Rear
GROUND CLEARANCE	7.0 in (18 cm)
CARGO DECK CAPACITY	9.6 cu ft (0.27 m³)
CARGO DECK MATERIAL	Roto-Molded Polyethylene
POWER	
POWER SOURCE	72V DC
HORSEPOWER (KW)	22.4HP (16.7 kW) - Measured at Peak Torque
ELECTRICAL SYSTEM	72V
BATTERY (QTY/TYPE)	Nine, 8V Deep Cycle
BATTERY CHARGER	900 Watt 72V DC
KEY OR PEDAL START	Pedal
SPEED CONTROLLER	350 Amp AC
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential w/ Helical Gears
GEAR SELECTION	Seatwrap-Mounted Forward-Neutral-Reverse
REAR AXLE RATIO	17:01
PERFORMANCE	
SEATING CAPACITY	2-Person (Bench)
WEIGHT W/O BATTERIES	873 lb (396 kg)
CURB WEIGHT	1440 lb (653 kg)
VEHICLE LOAD CAPACITY	900 lb (408 kg)
BED LOAD CAPACITY	500 lb (227 kg)
TOWING CAPACITY	930 lb (422 kg) Max Load
OUTSIDE CLEARANCE CIRCLE	24.0 ft (7.3 m)
SPEED	16 mph ± 0.5 mph (26 kph ± 0.8 kph)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack & Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	22 x 9 - 10 (4 Ply Rated)



COVERED WITH THE 2-YEAR CUSHMAN  
CARE TOTAL PROTECTION WARRANTY

[www.cushman.com](http://www.cushman.com)

©2016 Textron Specialized Vehicles Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

60007-G3 (Rev. 01/2016)