



CUSHMAN®

SHUTTLE 2



DELIVERS MORE THAN HARD WORK.

When you need to move large materials around your facility in a hurry, the Cushman® Shuttle 2 is the right choice. With a 1,200-pound cargo capacity and a 1.94 square metre cargo deck, it can move anything from event supplies to luggage. And whether it's equipped with a 48V DC electric drivetrain or a 13.5 hp EFI petrol engine, the Shuttle 2 offers plenty of power to get the job done right.

LET'S WORK.

13.5HP
EFI PETROL

48V
ELECTRIC
DRIVETRAIN

1.94sq M
CARGO DECK
CAPACITY



CUSHMAN® SHUTTLE 2



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Drop Side Rails
- Locking Glove Box
- Rear View Mirror
- Windshield
- Canopy
- Front Disc Brakes
- Pin Stripes
- Body Colour (Forest Green, White or Custom Options)
- Turn Signal with Four-Way Flashers
- Strobe Lights
- Beacon Light Kit
- Dome and Work Lights
- LED Headlights
- Hour Meter
- Fuse Cab
- Steel Cab and Doors
- Defroster
- Wheel Covers
- Limited Slip Differential

ELECTRIC MODEL		EFI PETROL MODEL
BODY & CHASSIS		
FRAME	Welded Steel w/ DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO (Front) / Steel Base Coat/Clear Coat (Rear)	
STANDARD COLOUR	Patriot Blue	
DIMENSIONS		
OVERALL LENGTH	358 cm (141.0 in)	
OVERALL WIDTH	123 cm (48.5 in)	
OVERALL HEIGHT	123 cm (48.6 in) (w/o Roof) / 183 cm (72.0 in) (w/ Struts & Roof)	
WHEEL BASE	237 cm (93.5 in)	
WHEEL TRACK	87 cm (34.2 in) Front / 97 cm (38.0 in) Rear	
GROUND CLEARANCE	11 cm (4.3 in)	12 cm (4.75 in)
CARGO DECK CAPACITY	1.94 m² (20.9 sq ft)	N/A
POWER		
POWER SOURCE	48V DC	4-Cycle, 24.5 ci (401cc)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	18.1 hp (13.5 kW)	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48V	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	Eight, 6V Deep Cycle	One, 12V Maintenance Free
BATTERY CHARGER	48 V, 120V AC, UL/CSA	N/A
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replacable Dry Cartridge
LUBRICATION	N/A	Pressurised Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	22.7 L (6 Gallon) Tank
SPEED CONTROLLER	400 Amp Precision Drive System (PDS)	N/A
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse	Forward - Reverse
REAR AXLE RATIO	14.7:1	11.47:1 (Forward) 14.35:1 (Reverse)
PERFORMANCE		
SEATING CAPACITY	2-Person	
WEIGHT W/O BATTERIES	367 kg (810 lb)	420 kg (926 lb)
CURB WEIGHT	590 kg (1300 lb)	N/A
VEHICLE LOAD CAPACITY	454 kg (1000 lb)	544 kg (1200 lb)
OUTSIDE CLEARANCE CIRCLE	7.8 m (25.5 ft)	7.8 m (25.5 ft)
SPEED	13 mph ± 0.5 mph (21 kph ± 0.8kph)	14 mph ± 0.5 mph (22.5 kph ± 0.8 kph)
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TYRES (FRONT & REAR)	18 x 8.50 - 8 (4 Ply Rated)"	

www.cushman.com +44(0)1473 270000

©2019 Textron Specialized Vehicles Inc. All specifications subject to change.

82282-G5 (Rev. 12/2018)