



CUSHMAN®

SHUTTLE 6



TRANSPORT LARGE GROUPS EFFICIENTLY.

The Cushman® Shuttle 6 is the go-to vehicle for moving people throughout a facility. With four forward-facing seats and a rear-facing bench seat, it can transport up to six people quickly and comfortably throughout your facility. Available with the option of an energy efficient 72V AC electric drivetrain or a 13.5 hp EFI petrol engine, the Shuttle 6 has the stamina necessary to take care of your personnel.

LET'S WORK.

13.5HP
EFI PETROL

72V
AC ELECTRIC
DRIVETRAIN

6
PERSON
SEATING
CAPACITY



CUSHMAN® SHUTTLE 6



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Rear View Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pin Stripes
- Body Colour (Forest Green, White or Custom Options)
- On Board Charger
- Turn Signal with Four-Way Flashers
- Brakelights
- LED Headlights
- CE Kit (petrol only)
- Wheel Covers
- Limited Slip Differential
- Trail Tyres



COVERED WITH THE 2-YEAR CUSHMAN
CARE TOTAL PROTECTION WARRANTY

ELECTRIC MODEL

EFI PETROL MODEL

BODY & CHASSIS

FRAME	Welded Steel w/ DuraShield Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOUR	Patriot Blue	

DIMENSIONS

OVERALL LENGTH	345 cm (136.0 in)	
OVERALL WIDTH	123 cm (48.5 in)	
OVERALL HEIGHT	123 cm (48.6 in) (w/o Roof) / 183 cm (72.0 in) (w/ Struts & Roof)	
WHEEL BASE	237 cm (93.5 in)	
WHEEL TRACK	87 cm (34.2 in) Front / 97 cm (38.0 in) Rear	
GROUND CLEARANCE	11 cm (4.3 in)	

POWER

POWER SOURCE	72V DC	4-Cycle, 24.5 ci (401cc)
VALVE TRAIN	22.4 hp (16.7 kW) Intermittent	Single Cylinder OHV
HORSEPOWER (KW)	72V	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	Six, 12 Volt Deep Cycle	Starter/Generator. Solid State Reg.
BATTERY CHARGER	1000 Watt, 72V, 120/230V VAC UL Listed	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replacable Dry Cartridge
LUBRICATION	N/A	Pressurised Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	22.7 L (6 Gallon) Tank
SPEED CONTROLLER	350 Amp AC	N/A
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse	Forward - Reverse
REAR AXLE RATIO	14.7:1	11.47:1 (Forward) 14.35:1 (Reverse)

PERFORMANCE

SEATING CAPACITY	6-Person	
WEIGHT W/O BATTERIES	437 kg (964 lb)	N/A
CURB WEIGHT	660 kg (1456 lb)	528 kg (1164 lb)
VEHICLE LOAD CAPACITY	544 kg (1200 lb)	
OUTSIDE CLEARANCE CIRCLE	7.8 m (25.5 ft)	7.8 m (25.5 ft)
SPEED	16.5 mph ± 0.5 mph (26.4 kph ± 0.8 kph) (High Speed) 12 mph ± 0.5 mph (19.3 kph ± 0.8 kph) (Low Speed)	16 mph ± 0.5 mph (26 kph ± 0.8 kph)

STEERING & SUSPENSION

STEERING	Self-Compensating Rack & Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TYRES (FRONT & REAR)	18 x 8.50 - 8 (4 Ply Rated)

www.cushman.com +44(0)1473 270000

©2019 Textron Specialized Vehicles Inc. All specifications subject to change.

82284-G7 (Rev. 12/2018)