



CUSHMAN®

SHUTTLE™ 8



EFFICIENT AND PRODUCTIVE HIGH VOLUME TRANSPORTATION.

The Cushman® Shuttle™ 8 is the right choice to move large groups of people throughout a campus or facility. With six forward-facing seats and a rear-facing bench seat, the Shuttle 8 can transport up to eight people quickly and comfortably. Available with either a 48V electric drivetrain or a 13.5 hp Kawasaki® gas-powered engine.

LET'S WORK.®

13.5HP
KAWASAKI®
GAS ENGINE
OPTION

48V
ELECTRIC
DRIVETRAIN
OPTION

8
PERSON
SEATING
CAPACITY



CUSHMAN® SHUTTLE™ 8



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Rear View Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pin Stripes
- Body Color (Forest Green, White, Ivory, Black or Custom Options)
- Turn Signal with Four-Way Flashers
- Brakelights
- LED Headlights
- CE Kit (gas only)



COVERED WITH THE 2-YEAR CUSHMAN
CARE TOTAL PROTECTION WARRANTY

ELECTRIC MODEL

GAS MODEL

| BODY & CHASSIS | |
|--------------------------|---|
| FRAME | Welded Steel w/ DuraShield™ Powder Coat |
| BODY & FINISH | Injection Molded TPO (Front) / Steel Base Coat/Clear Coat (Rear) |
| STANDARD COLOR | Patriot Blue |
| DIMENSIONS | |
| OVERALL LENGTH | 167.5 in (425 cm) |
| OVERALL WIDTH | 49.5 in (126 cm) |
| OVERALL HEIGHT | 45.5 in (116 cm) (w/o Roof) / 76.0 in (193 cm) (w/ Struts & Roof) |
| WHEEL BASE | 123.4 in (313 cm) |
| WHEEL TRACK | 36.0 in (91 cm) Front / 38.0 in (97 cm) Rear |
| GROUND CLEARANCE | 4.3 in (11 cm) |
| CARGO DECK CAPACITY | 400 lb (181 kg) |
| POWER | |
| POWER SOURCE | 48V DC |
| VALVE TRAIN | N/A |
| HORSEPOWER (KW) | 18.1 hp (13.5 kW) @1900 rpm |
| ELECTRICAL SYSTEM | 48V |
| BATTERY (QTY/TYPE) | Eight, 6V Deep Cycle |
| BATTERY CHARGER | 48V DC Delta Q, 120/230 VAC UL & CSA |
| KEY OR PEDAL START | Pedal |
| AIR CLEANER | N/A |
| LUBRICATION | N/A |
| OIL FILTER | N/A |
| COOLING SYSTEM | N/A |
| FUEL CAPACITY | N/A |
| SPEED CONTROLLER | 400 Amp Precision Drive System (PDS) |
| DRIVE TRAIN | Motor Shaft Direct Drive |
| TRANSAXLE | Differential w/ Helical Gears |
| GEAR SELECTION | Dash-Mounted Forward-Neutral-Reverse |
| REAR AXLE RATIO | 14.7:1 |
| PERFORMANCE | |
| SEATING CAPACITY | 8-Person |
| WEIGHT W/O BATTERIES | 1142 lb (518 kg) |
| CURB WEIGHT | 1632 lb (740 kg) |
| VEHICLE LOAD CAPACITY | 1600 lb (726 kg) |
| BED LOAD CAPACITY | 400 lb (181 kg) |
| OUTSIDE CLEARANCE CIRCLE | 33 ft (10 m) |
| SPEED | 13 mph ± 0.5 mph (21 kph ± 0.8kph) |
| STEERING & SUSPENSION | |
| STEERING | Self-Compensating Rack & Pinion |
| SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers |
| SERVICE BRAKE | 4-Wheel Hydraulic Brakes Front Disk, Rear Drum |
| PARKING BRAKE | Self-Compensating, Single-Point Engagement |
| TIRES (FRONT & REAR) | Kenda Load Star 50 psi (Front), 70 psi (Rear) |

www.cushman.com

©2016 Textron Specialized Vehicles Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82305-G3 (Rev. 01/2016)